

Pb	207
82	LEAD

LEAD IN CONSTRUCTION

Lead is a common hazardous element found at many construction sites. Lead exposure comes from inhaling fumes and dust, and lead can be ingested when hands are contaminated by lead dust. Lead can be taken home on workers' clothes, skin, hair, tools and in vehicles. Lead exposure may take place in demolition, salvage, removal, encapsulation, renovation and cleanup activities.

Avoid Exposure

- Use proper personal protective equipment (e.g., gloves, clothing and approved respirators).
- Wash hands and face after work and before eating, drinking and smoking.
- Never enter eating areas wearing protective equipment.
- Never wear away from work clothes and shoes that were worn during lead exposure.
- Launder clothing daily; use proper cleaning methods.
- Be alert to symptoms of lead exposure (e.g., severe abdominal pain, headaches, loss of motor coordination).

QC16

Use Respirators

- Wear appropriate respirators as directed.
- Conduct a user seal check each day before respirator use.
- Be aware of your company's respiratory protection program; understand the limitations and potential hazards of respirators.

Prevent Further Exposure

- Ensure adequate ventilation. When outdoors, stand upwind of any plume.
- Use dust collecting equipment when possible.
- Use lead-free materials and chemicals.
- Use wet methods to decrease dust.
- Use local exhaust ventilation for enclosed work areas.

Adapted from OSHA Quick Card 3291-10-05, U.S. Department of Labor.



Cherie Berry
Commissioner of Labor

Education, Training and Technical Assistance Bureau
919-807-2875 • 1-800-625-2267 • www.nclabor.com

Printed 9/07

500 copies of this public document were printed at a cost of \$40, or \$.08 per copy.